

TeraPrint Produktunterlage

Gebrandete TeraPrint-Downloadunterlage

PRODUKT	Der Inhaker® Messestand
UNTERLAGE	FSC Zertifikat Re-board
TYP	fire_certificate
ORIGINALSEITEN	2
STAND	16.06.2026
DATEI	products/pos-displays/assets/documents/697cebfec2e98d0a8a71196470e205d1e39b99615df6dafa4c112df7f63db1f0.pdf

Wichtig fuer die Produktion

Die folgenden Originalseiten bleiben in Format, Reihenfolge und Inhalt unveraendert.
Druckmass, Schnitt, Beschnitt, Sicherheitsbereiche und technische Vorlage wurden nicht veraendert.
Bei Zertifikaten, Datenblaettern und Pruefberichten bleiben Aussteller und Originalinhalte unveraendert.

TeraPrint Hinweis

Diese Datei ist lokal bei TeraPrint gespeichert und fuer den Kunden-Download vorbereitet.
Bitte bei Druckdaten immer die Massangaben und Beschnitt-/Sicherheitszonen der Originalvorlage beachten.
Bei Unsicherheit vor Bestellung oder Produktion TeraPrint kontaktieren.



Re-board® Basic is a lightweight yet exceptionally strong and fully recyclable paperboard. The unique engineered fluted core of Re-board® ensures excellent planar flatness combined with design flexibility to create almost any shape.

Printing and Finishing

Re-board® Basic can be digitally printed or finished with decorative laminates to achieve stunning results. It is a versatile board good printability and high performance. The unique engineered fluted core enables a Re-board® sheet to be rapidly cut into any conceivable shape.



The liner in Re-board® Basic is made of 100% recovered fibres from the Nordic countries making it one of the strongest board qualities on the market.

Exclusive Accessories

Re-board® comes with a wide range of exclusive accessories, including screws, edge bands, corner locks, hooks and more.



Sustainability

Re-board® Basic contains no harmful components and utilizes water-based adhesives. The board can be recycled as paper in normal waste paper streams found throughout the world.

Carbon Footprint

Re-board® is first rigid paperboard in the world to independently measure its CO2 emissions. 16mm Re-board CO2 emission/sqm = 2 kg, based on CEPI and ISO 14040 guidelines.



Certified Management Systems

The Norrköping mill is FSC Chain of Custody certified according to FSC-STD-40-004 ver 2.1.



The mark of
responsible forestry

Certified Management Systems

Re-board[®] Basic is produced in Norrköping, Sweden.

Technical Data	
Liner grammage (g/m ²)	325
Whiteness (ISO D65/10, %)	84
Brightness (ISO R457, %)	79
Width (mm)	1220, 1600
Length (mm)	Standard: 2200, 2400, 2440, 3200 Range: 1500-3500
Thickness (mm)	Standard: 10, 16 Range: 8-35
Weight (kg/sqm)	1.4 (10mm), 1.8 (16mm)
Tolerance, corner curvature from flat (mm)	<10
Tolerance in length, general (mm)	± 3

