

TeraPrint Produktunterlage

Gebrandete TeraPrint-Downloadunterlage

PRODUKT	Aufkleber auf Rolle
UNTERLAGE	Datenblatt weiß Temporär
TYP	datasheet
ORIGINALSEITEN	2
STAND	16.06.2026
DATEI	products/stickers-on-a-roll/assets/documents/7d3b8b81c6fcb8d4f9ebd18b9ced4386835d30ecb23ecf1e628d795741139345.pdf

Wichtig fuer die Produktion

Die folgenden Originalseiten bleiben in Format, Reihenfolge und Inhalt unverändert.
Druckmass, Schnitt, Beschnitt, Sicherheitsbereiche und technische Vorlage wurden nicht verändert.
Bei Zertifikaten, Datenblaettern und Pruefberichten bleiben Aussteller und Originalinhalte unverändert.

TeraPrint Hinweis

Diese Datei ist lokal bei TeraPrint gespeichert und fuer den Kunden-Download vorbereitet.
Bitte bei Druckdaten immer die Massangaben und Beschnitt-/Sicherheitszonen der Originalvorlage beachten.
Bei Unsicherheit vor Bestellung oder Produktion TeraPrint kontaktieren.

UPM Raflatac Technical Information

23-04-2023 EN SI

Product	PP WHITE FTC 60 / RR28 / HD-FSC
Sales Code	EYP/RR28/GHC
EAN	6415788282267
Product use	Multi-purpose product for rigid containers, where removability in combination with good water, chemical and oil resistance is needed. The product complies with EU regulations on food safety.

Typical technical values

Face		PP WHITE FTC 60	
Product	A white, glossy, biaxially oriented, cavitated, top-coated polypropylene film.		
Substance	46	g/m ²	ISO 536
Caliper	61	µm	ISO 534
Opacity	88	%	DIN 53146/1
Printability	Suitable for flexography, screen, offset, UV inkjet and Xeikon printing methods. Thermal transfer is possible with selected wax-resin and resin ribbons.		
Adhesive		RR28	
Type	Removable adhesive for filmic labels.		
Composition	Acrylic, water borne.		
Tack	6	N/25mm	FTM 9
Peel 90°	6	N/25mm	FTM 2
Backing		HD-FSC	
Product	A white transparent glassine backing paper.		
Substance	57	g/m ²	ISO 536
Caliper	50	µm	ISO 534
Tensile strength MD	6	kN/m	ISO 1924
Tensile strength CD	2,3	kN/m	ISO 1924
Transparency	50	%	DIN 53147
Sustainability	The product is sold as FSC Mix Credit under UPM Raflatac's FSC™ certificate SGSCH-COC-004879.		
Performance			
Total caliper	130 µm ± 10%		
labelling temperature	5 °C		
Service temperature	-10 °C to 80 °C		
Shelf life	From date of manufacture: 24 months, under FINAT defined storage conditions (+20-25°C and RH 40-50%). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.		

Approvals

Approvals

For further compliance information related to food labeling applications, please contact your local sales representative for a Declaration of Conformance (DoC) document.

Disclaimer

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

